

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

JP 360202956 A
OCT 1985

(54) CIRCUIT MODULE

(11) 60-202956 (A)

(43) 14.10.1985 (19) JP

(21) Appl. No. 59-58240


(22) 28.3.1984

(71) HITACHI SEISAKUSHO K.K. (72) BUNICHI TAGAMI(1)

(51) Int. Cl. H01L23 36


PURPOSE: To ensure the area of heat dissipation even when region on which parts are not loaded is generated by fitting a dummy radiator fin to a circuit module consisting of a plurality of semiconductor elements.

CONSTITUTION: Chip carriers 2 on which semiconductor integrated circuit elements are mounted are placed on a ceramic wiring substrate 1, and radiator fins are fitted to the chip carriers 2. Leads 4 connect signals and supply a power supply with electricity. Dummy fins 10 are loaded in place of parts, and heat generated in each element is mainly dissipated from the radiator fins 3, but one part transmits the wiring substrate 1 and is dissipated from the dummy fins 10.




057/722


第 1 圖



第 2 圖



第 3 圖



第 4 圖

